GENERAL

aenor norma une en 60617 2 1997

Published: September 19, 2026 | Index ID: #-

Introduction: Why Standards Matter in Engineering Drawings

When an engineer sketches a component, designs a complex system, or communicates a product idea, the drawing becomes the language that engineers, manufacturers, and suppliers share. Without a common vocabulary, a single symbol can be misinterpreted, leading to costly design changes, production delays, or even safety hazards. That is why standardization bodies such as the **AENOR**(Spanish Association for Standardization) exist—to create a universal set of rules that guarantees clarity, consistency, and efficiency across the entire engineering ecosystem.

One of the most widely adopted standards in this domain is the **UNE EN 60617-2:1997**. It defines a comprehensive set of symbols for use in engineering drawings, ensuring that professionals from all backgrounds can read and create designs with confidence. In this article, we will dive deep into what this standard covers, why it matters, and how you can integrate it into your design workflow.

What Is UNE EN 60617-2:1997?

UNE EN 60617-2:1997 is the Spanish national implementation of the European standard **EN 60617-2**, which itself is a part of the broader **ISO 1063** family of technical drawing standards. The 1997 edition was published by AENOR to align Spain's engineering practices with the European and international community. The standard focuses on **general symbols for engineering drawing**—the graphical representations of mechanical features, materials, and processes that appear in technical documents.

While part 1 of the standard (UNE EN 60617-1) deals with the rules for creating and presenting drawings, part 2 provides the actual symbol set. The two parts together form a complete toolkit for producing clear, professional technical drawings.

Historical Context: From ISO to UNE

The roots of UNE EN 60617-2 trace back to the early 1980s when the **ISO 1063**standard was first introduced. ISO 1063 was designed to standardize symbols used in engineering drawings worldwide, but as engineering practices evolved, the need for a more detailed and regionally tailored set of symbols became apparent.

In 1993, the European Committee for Standardization (CEN) adopted **EN 60617** as the European standard for engineering symbols. This standard was then harmonized with ISO 1063, resulting in the dual numbering system: **ISO 1063** (international) and **EN 60617**(European). AENOR subsequently translated and adapted the standard for Spanish users, publishing UNE EN 60617-2:1997 in 1997 to ensure compliance with European regulations and to facilitate cross-border engineering projects.

Structure of the Standard

UNE EN 60617-2:1997 is organized into several sections that guide users through the selection and application of symbols. The main components include:

1. Scope and Purpose – Defines the standard's applicability to mechanical, electrical, civil, and industrial

engineering drawings.

2. Definitions and Terminology – Provides clear explanations of key terms such as “symbol,” “notation,” and “drawing element.”
3. General Rules – Establishes guidelines for symbol placement, size, line weight, and orientation.
4. Symbol Sets – Divides symbols into categories: mechanical features, surface textures, materials, manufacturing processes, and more.
5. Examples and Illustrations – Offers practical examples of how symbols should appear in real drawings.
6. Appendices – Contains supplementary tables and references for quick lookup.

By following these sections, engineers can ensure that every symbol they use is compliant with the standard, thereby avoiding ambiguity.

Key Symbols and Their Meanings

Below is a selection of some of the most frequently used symbols in UNE EN 60617-2, grouped by category. Each symbol is accompanied by a brief description of its purpose and typical application.

Mechanical Features

- Circle (Ø) – Denotes a hole or bore. The diameter is indicated inside the circle.
- Square (%¡) – Represents a rectangular hole or slot.
- Triangle (%³) – Used for keyways or notches.
- Line with arrowheads – Indicates the direction of a feature, such as a groove or a cam profile.

Surface Textures

- Roughness symbol (R) – Indicates a rough surface finish.
- Polished symbol (P) – Represents a polished or mirror-like finish.
- Honed symbol (H) – Denotes a honed surface, typically used in bearings.

Materials

- Steel (S) – Represents standard structural steel.
- Aluminum (A) – Indicates aluminum alloys.
- Stainless steel (SS) – Used for corrosion-resistant steel components.

Manufacturing Processes

- CNC (Computer Numerical Control) – Symbolized by a gear icon with a computer mouse.
- Welding (W) – Represented by a series of intersecting lines.
- Heat treatment (HT) – Depicted by a flame icon.

How to Apply UNE EN 60617-2 in Practice

Implementing the standard correctly requires a systematic approach. The following steps outline a practical workflow for engineers and CAD professionals.

1. Familiarize Yourself with the Symbol Catalog – Download the official symbol set from AENOR’s website or your CAD vendor’s library.
2. Define a Drawing Template – Create a template that includes standard margins, title blocks, and a predefined layer structure for symbols.
3. Use Layer Management – Assign each symbol category to its own layer (e.g., Mechanical Features, Materials) to maintain clarity.
4. Apply Consistent Line Weights – Follow the standard’s guidelines for line thickness; typically, main features

use a heavier line weight than auxiliary annotations.

5. Verify Symbol Placement – Ensure symbols are placed in the correct orientation and position relative to the feature they represent.
6. Include Descriptive Text – Complement symbols with concise text (e.g., Ø 12 mm) to avoid ambiguity.
7. Validate Against the Standard – Use a checklist to confirm that all symbols comply with the standard's rules.
8. Export and Archive – Save drawings in a standardized format (e.g., DWG, DXF) and archive them in a central repository.

By following this workflow, you reduce the risk of misinterpretation and streamline the review process.

Integration with CAD Software

Modern CAD packages such as AutoCAD, SolidWorks, and CATIA provide built-in libraries that include UNE EN 60617 symbols. Here's how you can make the most of these tools:

- Import Symbol Libraries – Most CAD vendors offer downloadable libraries that can be imported directly into your drawing environment.
- Create Custom Blocks – For symbols not included in the standard set, create custom blocks and assign them the appropriate layer.
- Use Annotation Styles – Configure annotation styles to automatically apply the correct line weight, font, and size.
- Automate Symbol Placement – Leverage CAD's scripting capabilities (e.g., AutoLISP for AutoCAD) to automate repetitive symbol placement tasks.
- Validate with Add-Ons – Some CAD add-ons can automatically check compliance with UNE EN 60617-2, flagging any deviations.

By integrating the standard into your CAD workflow, you ensure consistency across all drawings and reduce manual errors.

Benefits of Using UNE EN 60617-2

Adopting this standard offers numerous advantages for engineering teams, manufacturers, and clients alike.

- Clear Communication – A universal set of symbols eliminates language barriers and misinterpretation.
- Reduced Rework – Standardized drawings minimize design changes caused by unclear annotations.
- Compliance with Regulatory Bodies – Many regulatory agencies require adherence to ISO/EN standards for product certification.
- Improved Collaboration – Designers, fabricators, and quality control teams can work together more efficiently.
- Time and Cost Savings – Consistent symbols speed up the drafting process and reduce the need for revisions.
- Future-Proofing – Aligning with international standards ensures that your drawings remain relevant as new technologies emerge.

Common Pitfalls and How to Avoid Them

Even experienced engineers can fall into common mistakes when using UNE EN 60617-2. Being aware of these pitfalls helps maintain drawing quality.

1. Inconsistent Symbol Size – Always use the line weights specified in the standard. Deviating from the recommended thickness can obscure details.
2. Misplaced Symbols – Place symbols in the correct orientation relative to the feature. For example, a hole

symbol should be centered on the hole's location.

3. Overloading the Drawing – Avoid adding unnecessary symbols that clutter the drawing. Use only what is essential for understanding the design.

4. Ignoring Textual Annotations – Symbols should be complemented by clear text. Relying solely on symbols can lead to confusion.

5. Not Updating Symbol Libraries – Keep your symbol libraries current. New revisions of UNE EN 60617 may introduce updated symbols or corrections.

Comparing UNE EN 60617-2 with Other Standards

While UNE EN 60617-2 is widely used in Spain and many European countries, other standards exist that may be relevant depending on your industry or region.

Baca Juga (Artikel Terkait)

- **advanced engineering electromagnetics solution manual edition hardcover by balanis constantine a published by wiley**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-solution-manual-edition-hardcover-by-balanis-constantine-a-published-by-wiley.pdf
- **advanced engineering electromagnetics solutions manual**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-solutions-manual.pdf
- **advanced engineering electromagnetics wiley 1989 grading**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-wiley-1989-grading.pdf
- **advanced engineering fluid mechanics by biswas**
  URL: http://blueesystems.com/advanced-engineering-fluid-mechanics-by-biswas.pdf

Tags: #aenor #norma #une