GENERAL

what is hub in networking

Published: September 3, 2026 | Index ID: #-

Introduction

When you first step into the world of networking, terms like router, switch, and hub appear almost as if they were a secret code. Among these, the hub is perhaps the most straightforward yet historically significant device that has shaped how we connect computers and other devices. Understanding **what is hub in networking**is essential for anyone—from budding IT professionals to hobbyists who want to build a home network—because it reveals the foundational principles of data transmission, network topology, and the evolution of networking hardware.

In this article we will explore the hub in depth: its definition, how it works, the differences between hubs, switches, and routers, and why modern networks are moving away from hubs. We will also cover practical tips for setting up a hub, troubleshooting common issues, and evaluating whether a hub is still useful in today's high-speed, security focused networking environments. By the end, you'll have a clear, comprehensive picture of what a hub is, how it fits into the larger networking ecosystem, and why it matters.

Understanding the Basics of Networking

What Is a Network?

A network is simply a collection of devices—computers, printers, servers, mobile phones, and more—that are connected so they can share resources and communicate. The most common type of network is a Local Area Network (LAN), which typically covers a single building or campus. Networks rely on protocols such as TCP/IP to ensure that data packets travel reliably from one device to another.

Core Networking Devices

- Router – Directs traffic between different networks, such as a home LAN and the Internet.
- Switch – Connects devices within the same network, intelligently forwarding data only to the intended recipient.
- Hub – A basic, non intelligent device that broadcasts incoming data to all connected devices.
- Modem – Converts digital data from a computer into a form suitable for transmission over a telephone line or cable system.
- Access Point (AP) – Extends a wired network to wireless devices.

The Role of a Hub in Networking

Definition and Function

A hub is a networking device that connects multiple Ethernet devices, making them act as a single network segment. Unlike a switch, a hub does not keep track of which device is connected to which port. Instead, it simply takes any incoming data and repeats it to all other ports, a process known as **broadcasting**. Because of this, every device on the network receives every packet, regardless of its intended destination.

How a Hub Works

When a device sends data to a hub, the hub receives the signal and then transmits that signal out on all other ports simultaneously. This is why hubs operate in a **collision domain**, where multiple devices may try to send data at the

same time, causing collisions that must be resolved by retransmission. The simplicity of this design makes hubs inexpensive and easy to use, but it also limits performance and introduces security concerns.

Types of Hubs

- Passive Hub – Simply forwards data without amplification. It is rarely used today because it does not regenerate signals.
- Active Hub – Amplifies and regenerates signals, allowing for longer cable runs and better performance.
- 10/100/1000Mbps Hubs – Support varying speeds from 10 /Mbps (Ethernet), 100 /Mbps (Fast Ethernet), to 1 /Gbps (Gigabit Ethernet).
- PoE Hub – Provides Power over Ethernet, allowing connected devices to receive both data and electrical power through the same cable.

Hub vs Switch vs Router

Key Differences

While all three devices connect network segments, they differ significantly in intelligence, speed, and functionality:

- Hub – Broadcasts all traffic; no MAC address table; slower due to collisions.
- Switch – Maintains a MAC address table; forwards frames only to the intended port; supports full duplex communication.
- Router – Operates at Layer /3 (network layer); routes packets between different networks using IP addresses.

When to Use Each Device

Choosing between a hub, switch, or router depends on the network's size, performance requirements, and budget:

1. Small home or office network with a few devices – A hub can be adequate if performance demands are low.
2. Growing network with multiple devices and higher throughput – A switch is the preferred choice due to its efficiency.
3. Connecting multiple networks or providing Internet access – A router is essential for routing traffic and managing IP addresses.

Performance and Security Considerations

Because hubs broadcast all traffic, they can create network bottlenecks and increase the likelihood of data collisions. Additionally, every device on the network can see all traffic, raising privacy and security concerns. Switches mitigate these issues by limiting traffic to the intended recipient and often support features such as VLANs (Virtual Local Area Networks) for segmentation and security.

Technical Aspects of a Hub

Signal Transmission

Hubs use either **unshielded twisted pair (UTP)** or **shielded twisted pair (STP)**cables to transmit data. In a typical Ethernet setup, a hub receives a signal from a device, amplifies it if necessary, and then retransmits it to all other ports.

Collision Domains

In a hub based network, all ports share a single collision domain. When two devices transmit simultaneously, a collision occurs, and the data must be retransmitted. This reduces overall network throughput, especially as the number of devices increases.

Broadcast Domains

A broadcast domain is the set of all devices that can receive broadcast frames from each other. Hubs create a single broadcast domain for all connected devices, meaning that broadcast traffic is shared across the entire network segment.

Speed and Duplex Modes

Modern hubs support 10/100/1000 Mbps speeds and can operate in half duplex or full duplex mode. However, most hubs are limited to half duplex operation due to their broadcasting nature, which can lead to reduced performance compared to full duplex switches.

Setting Up a Hub in Your Network

Planning Your Network Layout

Before adding a hub, map out the physical layout of your network: identify device locations, cable runs, and potential interference sources. Hubs are best suited for short cable runs (typically up to 100 meters for 100 Mbps networks) and environments where device density is low.

Connecting Devices to a Hub

To connect a device to a hub:

1. Use a standard Ethernet cable (Cat /5e or higher for Gigabit speeds).
2. Plug one end into the device's Ethernet port.
3. Plug the other end into an available port on the hub.
4. Repeat for additional devices.

Ensure that all connections are secure and that the hub's power supply is properly connected.

Testing and Troubleshooting

After connecting devices, perform the following checks:

- Verify link lights on the hub and connected devices.
- Run a simple ping test between devices to confirm connectivity.
- Use network monitoring tools (e.g., Wireshark) to detect collisions or excessive broadcast traffic.
- Check for any error counters on the hub's management interface, if available.

If you encounter high collision rates or slow performance, consider replacing the hub with a switch or adding a network segment.

Pros and Cons of Using a Hub

Advantages

- Low Cost – Hubs are inexpensive compared to switches.
- Ease of Use – No configuration required; plug and play.
- Compatibility – Works with all Ethernet devices, including legacy equipment.

Disadvantages

- Performance Limitations – Broadcast and collision domains reduce throughput.
- Security Risks – All devices can see all traffic, exposing sensitive data.
- Scalability Issues – Adding more devices quickly degrades performance.
- Lack of Management Features – No support for VLANs, QoS, or port mirroring.

Future of Hubs in Modern Networks

Shift to Switches and Wireless

As network demands grow—higher bandwidth, lower latency, and stronger security—hubs have largely been phased out in favor of managed switches and wireless access points. The industry's focus on **software defined networking (SDN)** and **network function virtualization (NFV)** further reduces the need for simple hardware hubs.

Legacy Systems and Compatibility

Despite their obsolescence, hubs still find a niche in environments that rely on legacy hardware, such as industrial control systems or older office setups. In these cases, a hub's simplicity can be an advantage, provided that the network's performance and security requirements are modest.

Conclusion

Understanding **what is hub in networking**offers insight into the evolution of network infrastructure and the trade offs between simplicity and performance. While hubs are inexpensive and straightforward, their broadcasting nature leads to collisions, limited throughput, and security vulnerabilities—issues that modern switches and routers address efficiently. For most contemporary networks, a switch or wireless access point is the recommended choice. However, hubs remain useful in certain legacy or low traffic scenarios where budget constraints and device compatibility are paramount.

Baca Juga (Artikel Terkait)

- **advanced engineering electromagnetics solution manual edition hardcover by balanis constantine a published by wiley**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-solution-manual-edition-hardcover-by-balanis-constantine-a-published-by-wiley.pdf
- **advanced engineering electromagnetics solutions manual**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-solutions-manual.pdf
- **advanced engineering electromagnetics wiley 1989 grading**
  URL: http://blueesystems.com/advanced-engineering-electromagnetics-wiley-1989-grading.pdf
- **advanced engineering fluid mechanics by biswas**
  URL: http://blueesystems.com/advanced-engineering-fluid-mechanics-by-biswas.pdf

Tags: #what #networking